

- Quick mounting.
- No condensation
- Quick and simple maintenance
- Designed for working with no filter.
- Filter is optional for severe environments.
- ALUZINC structure: rust free for more than 600 hours in saline fog.

Models	Voltage Frequency	Version (V)	Compliance	Certification on demand
MKP1121PU	1~ 115V 50/60Hz	1	CE	CSF US
MKP1121RH	2~ 400V 50/60Hz	1	CE	CSF US
MKP1121TH	1~ 230V 50/60Hz	1	CE	CSF US
MKP1122TH	1~ 230V 50/60Hz	2	CE	CSF US
MKP1023RH	2~ 400V 50/60Hz	3	CE	
MKP1023TH	1~ 230V 50/60Hz	3	CE	

On demand: Different voltage; Stainless steel(AISI304) cover; Special painting.

Version available:

(V) 0 = Electromechanical thermostat control.

(V) 1 = Electromechanical thermostat + alarm signal.

(V) 2 = Electromechanical thermostat + alarm signal + door open checking device.

(V) 3 = Electronic thermostat + display + alarm signal + door open checking device.

(V) 4 = Electronic thermostat + display + alarm signal.

(V) 5 = Electronic thermostat(NO display) + alarm signal.


(V) U = MKP112\*U



Available accessories	Semi-recessed mounting casing	See reference sheet
	External side protection IP54	See reference sheet
	Filter kit	See reference sheet
	Spare filter set	See reference sheet
	Drainage condensation connector	
	Dissipator of condensation	

Operating voltage ±10%	Voltage	I rated 50/60 Hz	I start-up 50/60 Hz	Protection fuse	MCA
	1~ 230V	2,9/3,7 A	11,7/15 A	T6 A	4,6/5,6 A
	1~ 115V	5,5/6,3 A	25/28 A	T12 A	7,6/8,5 A
	2~ 400V	1,7/2,1 A	7,1/6,9 A	T3A	

Technical data		Frequency 50/60 Hz	
Cooling power	A35-A35	0,96 / 1,05 kW	[ 3276 / 3583 Btu/h ]
	A50-A35	0,78 / 0,82 kW	[ 2662 / 2798 Btu/h ]
Absorbed electrical power	A35-A35	0,50 / 0,60 kW	
	A50-A35	0,58 / 0,69 kW	
Energy efficiency EER	A35-A35	1,9 / 1,8	
Fan flow rate	ext. cabinet	350 / 385 m3/h	
	int. cabinet	350 / 385 m3/h	
Cooling gas		R134a	
Max pressure		2,4 MPa	[ 348 psi ]
Temperature range: setting 35°C [ 95°F ]	ext. cabinet	20÷55 °C	[ 68÷131 °F ]
	int. cabinet	20÷50 °C	[ 68÷122 °F ]
Noise level		67 dB(A)	
Weight		33 kg	[ 72,75 lb ]
Continuous duty		100%	
Protection standard	ext. Cabinet	IP 34	
	int. cabinet	IP 55	
Standard colour	Embossed	RAL 7035	
Power connection		Cable 3 m	[ 9,84 ft ]
Dimensions	W x H x D	350x800x195 mm	[ 13,78x31,5x7,68 in ]
Installation environment		Indoor	



## WALL MOUNTED MODEL

1000 W

