

- Quick mounting.
- No condensation + integrated evaporation sistem + No seepage inside cabinet
- Quick and simple maintenance
- Designed for working with no filter.
- Filter is optional for severe environments.
- ALUZINC structure: rust free for more than 600 hours in saline fog.

Models	Voltage Frequency	Version (V)	Compliance	Certification on demand
MKT2021TH	1~ 230V 50/60Hz	1	CE	
MKT2022TH	1~ 230V 50/60Hz	2	CE	
MKT2021RH	2~ 400V 50/60Hz	1	CE	

On demand: Different voltage; Stainless steel(AISI304) cover; Special painting.

Available version:

(V) 0 = Electromechanical thermostat control.

(V) 1 = Electromechanical thermostat + alarm signal.

(V) 2 = Electromechanical thermostat + alarm signal + door open checking device.

(V) 3 = Electronic thermostat + display + alarm signal + door open checking device.



(V) 4 = Electronic thermostat + display + alarm signal.

(V) 5 = Electronic thermostat(NO display) + alarm signal.

Available accessories	Filter kit	See reference sheet
	Spare filter set	See reference sheet
	Condensation checking device	
	Drainage condensation connector	

Operating voltage ±10%	Voltage	I rated 50/60 Hz	I start-up 50/60 Hz	Protection fuse	MCA
	1~ 230V	4,0/4,3 A	21,8 / 24 A	T8 A	6,4 A
	2~ 400V	2,3/2,5 A	12 / 13,2 A	T8 A	4,1 A

Technical data		Frequency 50/60 Hz	
Cooling power	A35-A35	1,9 / 2,05 kW	[6483 / 7001 Btu/h]
	A50-A35	1,4 / 1,5 kW	[4777 / 5159 Btu/h]
Absorbed electrical power	A35-A35	0,9 / 1,0 kW	
	A50-A35	1,1 / 1,5 kW	
Energy efficiency EER	A35-A35	2,1 / 2,0	
Fan flow rate	ext. cabinet	620 / 680 m3/h	
	int. cabinet	550 / 600 m3/h	
Cooling gas		R134a	
Max pressure		2,4 MPa	[348 psi]
Temperature range: setting 35°C [95°F]	ext. cabinet	20÷55 °C	[68÷131 °F]
	int. cabinet	20÷50 °C	[68÷122 °F]
Noise level		69 dB(A)	
Weight		47 kg	[103,61 lb]
Continuous duty		100%	
Protection standard	ext. Cabinet	IP 34	
	int. cabinet	IP 54	
Standard colour	Embossed	RAL 7035	
Power connection		Cable 3 m	[9,84 ft]
Dimensions	W x H x D	700x400x430 mm	[27,56x15,75x16,93 in]
Installation environment		Indoor	



TOP MOUNTED MODEL

1900 W

