

- Fixing by Elastic hooks (otherwise by four self-threading screws).
- It is important that the ambient was cleaned and the external temperature was lower than the internal one.
- Each filter fan needs a specific filter grill (MGF) for the inlet and outlet airflow.
- Using the continues current version you avoid all kind of interference
- Each model can be transformed, on request, in extracting version with a rotation of the fan (Version V = 1).
- Filter elements are made of unbreakable synthetic fibre and can be easily cleaned by rinsing or shaking. A 6 spare filter elements kit (PF***) can be provided, upon request, for each fan model.
- Type of material: ABS/PC alloy according to UL94V0.
- Storage temperature: -45°C to +75°C.
- Lifetime L10 at 40°C: 50.000h.
- Type of Filter Element: Self-Extinguishing.
- Type of Bearing: Shielded Ball.
- Filtering Class: Class G3 according to EN 779 (EU4 DIN 24185).
- Separation Degree: 85% - DIN 24185.
- Dust Retention Capacity: 600g/m².
- Filter Element is washable for about 10 times.
- Standard Colour: RAL7035


Filter and fan		MVP023(V)*TE	MVP023(V)*PE	MVP023(V)*JE
voltage rated/ current rated	50Hz	230V/70mA	115V/140mA	24V DC/190 mA
	60Hz	230V/60mA	115V/120mA	
Filter grill		MGF023E		
Max Air Flow		23 / 30 m³/h	23 / 30 m³/h	33 m³/h
Air rate with filter grill		1 x MGF023E: 15/18 m³/h		
Power	50Hz	14 W	12 W	4,56 W
	60Hz	12 W	9 W	
Noise level	50Hz	32 dB(A)		38 dB(A)
	60Hz	36 dB(A)		
Temperature range		From -10°C to +55°C		
Protection standard		IP54 Standard.		
* Version(V)		(V)0 = Blow-Into → (V)1 = Extracting ←		
Drilling Template		□ 91,5 mm (0+1,5)		
Available accessories		Spare filter kit PF***.		

Filter and fan		MVP063(V)*TE	MVP063(V)*PE	MVP063(V)*JE
voltage rated/ current rated	50Hz	230 V/ 100 mA	115 V/ 200 mA	24V DC/300 mA
	60Hz	230 V/ 80 mA	115 V/ 160 mA	
Filter grill		MGF063E		
Fan air flow <i>free flow</i>		57 / 61 m³/h	57 / 61 m³/h	85 m³/h
Air rate with filter grill		1 x MGF063E: 43/50 m³/h		
Power	50Hz	17 W	14 W	7,2 W
	60Hz	15 W	12 W	
Noise level	50Hz	42 dB(A)		47 dB(A)
	60Hz	46 dB(A)		
Temperature range		-10° C +55° C		
Protection standard		IP54 Standard.		
* Version(V)		(V)0 = Blow-Into → (V)1 = Extracting ←		
Drilling Template		□ 125 mm (0+1,5)		
Available accessories		Spare filter kit PF***		

WALL MOUNTING MODEL

20-70m³/h

MVP023xxx



MVP063xxx

