

- Quick mounting.
- No condensation
- Quick and simple maintenance
- Designed for working with no filter.

- Filter is optional for severe environments.
- ALUZINC structure: rust free for more than 600 hours in saline fog.
- Extra Slim(76mm) - High Power.

Models	Voltage Frequency	Version (V)	Compliance	Certification on demand
MKP1111TEI	1~ 230V 50/60Hz	1 + I	CE	
MKP1111REI	2~ 400V 50/60Hz	1 + I	CE	
MKP1116TEI	1~ 230V 50/60Hz	6 + I	CE	

On demand: Different voltage; Stainless steel(AISI304) cover; Special painting.

Versions:

(V) 1 = Electromechanical thermostat + alarm signal.

(V) 2 = Electromechanical thermostat + alarm signal + door open checking device.

(V) 3 = Electronic thermostat + display + alarm signal + door open checking device.

(V) 4 = Electronic thermostat + display + alarm signal.



(V) 6 = Electromechanical thermostat + alarm signal + remote control.

(V) I = Recessed mounting.

Available accessories	Filter kit	See reference sheet
	Spare filter set	See reference sheet
	Dissipator of condensation	

Operating voltage ±10%	Voltage	I rated 50/60 Hz	I start-up 50/60 Hz	Protection fuse	MCA
	1~ 230V	3,8/4,0 A	14,8/17 A	T6 A	
	2~ 400V	2,2/2,3 A	8,5/10,5 A	T6 A	

Technical data		Frequency 50/60 Hz	
Cooling power	A35-A35	1,1 / 1,2 kW	[ 3754 / 4095 Btu/h ]
	A50-A35	0,85 / 0,9 kW	[ 2900 / 3071 Btu/h ]
Absorbed electrical power	A35-A35	0,87 / 0,92 kW	
	A50-A35	0,99 / 1,1 kW	
Energy efficiency EER	A35-A35	1,3 / 1,3	
Fan flow rate	ext. cabinet	860 / 900 m <sup>3</sup> /h	
	int. cabinet	570 / 620 m <sup>3</sup> /h	
Cooling gas		R134a	
Max pressure		2,4 MPa	[ 348 psi ]
Temperature range: setting 35°C [95 F]	ext. cabinet	20÷55 / 20÷50 °C	[ 68÷131 / 68÷122 F]
	int. cabinet	20÷50 / 20÷45 °C	[ 68÷122 / 68÷113 F]
Noise level		67 dB(A)	
Weight		42 kg	[ 92,6 lb ]
Continuous duty		100%	
Protection standard	ext. Cabinet	IP 34	
	int. cabinet	IP 55	
Standard colour	Embossed	RAL 7035	
Power connection		Connector	
Dimensions	W x H x D	495x1640x162 mm	[ 19,49x64,57x6,38 in ]
Installation environment		Indoor	



## WALL MOUNTED MODEL

1100 W

