

- Roof enclosure mounting.
 - Evaporation of condensate.
 - Designed for working with no filter.
 - Easy and fast maintenance.
 - ALUZINC structure: rust free for more than 500 hours in saline fog.
- Filter is optional for severe environments.

Models	Voltage Frequency	Version (V)	Compliance	Certification
MKT1721TE	230V~ 50/60 Hz	1	CE	
MKT1721RE	400 V~ 50/60 Hz	1	CE	

(V) 0 = electromechanical thermostat control

(V) 1 = thermostat control + alarm signal


(V) 2 = thermostat control + alarm signal + door open

Available accessories	Filter Kit (2 versions)	See sheet BA020X
	Spare Filter Set.	See sheet BA030X
	Condensate check kit.	See sheet BA080X

On demand (for sufficient quantities): 1.4301 Stainless Steel case or special painting.

Operating voltage ±10%	Voltage	I rated 50/60 Hz	I start-up 50/60 Hz	Protection fuse	MCA
	230 V ~	4,2 / 4,8 A	15,9/18,3 A	T6 A	
	400 V ~	2,4 / 2,8 A	9,2/10,6 A	T4 A	

Technical data		Frequency 50/60 Hz	
Cooling power	A35-A35	1,52 / 1,64 kW	[5189/5599 Btu/h]
	A50-A35	1,25 / 1,35 kW	[4268/4609 Btu/h]
Absorbed electrical power	A35-A35	0,79 / 0,91 kW	
	A50-A35	0,91 / 1,1 kW	
Energy efficiency ratio EER	A35-A35	1,9 / 1,8	
Fan flow rate	ext.cabinet	620 / 680 m ³ /h	
	int.cabinet	400 / 440 m ³ /h	
Cooling gas		R134a	
Max pressure		2,4 MPa	[348 psi]
Temperature range setting 35 °C [95 °F]	ext.cabinet	20÷50 °C	[68÷122 °F]
	int.cabinet	20÷45 °C	[68÷113 °F]
Noise level		67 dB(A)	
Weight (+5 kg [11 lb] RE models)		45 kg	[99,0 lb]
Continuous duty		100%	
Protection standard	ext.cabinet	IP 34	
	int.cabinet	IP 54	
Standard colour	embossed	RAL 7035	
Connection		Cable 3 m	[9,84 ft]
Dimensions	L x H x P	700x400x400 mm	[27,6x15,7x15,7 in]
Installation environment		Indoor	



TOP MOUNTED MODEL

1500 W

