

- Quick mounting.
- No condensation + integrated evaporation sistem + No seepage inside cabinet
- Quick and simple maintenance
- Designed for working with no filter.
- Filter is optional for severe environments.
- ALUZINC structure: rust free for more than 600 hours in saline fog.

Models	Voltage Frequency	Version (V)	Compliance	Certification on demand
MKT2021BH	3~ 400V 50 Hz 3~ 440V 60 Hz	1	CE	
MKT2022BH	3~ 400V 50 Hz 3~ 440V 60 Hz	2	CE	
MKT2023BH	3~ 400V 50 Hz 3~ 440V 60 Hz	3	CE	

On demand: Different voltage; Stainless steel(AISI304) cover; Special painting.

Available version:

(V) 0 = Electromechanical thermostat control.

(V) 1 = Electromechanical thermostat + alarm signal.

(V) 2 = Electromechanical thermostat + alarm signal + door open checking device.



(V) 3 = Electronic thermostat + display + alarm signal + door open checking device.

(V) 4 = Electronic thermostat + display + alarm signal.

Available accessories	Filter kit	See reference sheet
	Spare filter set	See reference sheet
	Condensation checking device	
	Drainage condensation connector	

Operating voltage ±10%	Voltage	I rated	I start-up	Protection	MCA
	3~ 400V 50 Hz	2,1 A	9,4 A	T6 A	
	3~ 440V 60 Hz	2,3 A	10,3 A	T6 A	3,8 A

Technical data		Frequency 50/60 Hz	
Cooling power	A35-A35	1,9 / 2,05 kW	[ 6483 / 7001 Btu/h ]
	A50-A35	1,6 / 1,7 kW	[ 5459 / 5896 Btu/h ]
Absorbed electrical power	A35-A35	0,98 / 1,1 Kw	
	A50-A35	1,2 / 1,7 kW	
Energy efficiency EER	A35-A35	2,0 / 1,9	
Fan flow rate	ext. cabinet	620 / 680 m3/h	
	int. cabinet	550 / 600 m3/h	
Cooling gas		R134a	
Max pressure		2,4 MPa	[ 348 psi ]
Temperature range: setting 35°C [ 95°F ]	ext. cabinet	20÷55 °C	[ 68÷131 °F ]
	int. cabinet	20÷50 °C	[ 68÷122 °F ]
Noise level		69 dB(A)	
Weight		47 kg	[ 103,61 lb ]
Continuous duty		100%	
Protection standard	ext. Cabinet	IP 34	
	int. cabinet	IP 54	
Standard colour	Embossed	RAL 7035	
Power connection		Cable 3 m	[ 9,84 ft ]
Dimensions	W x H x D	700x400x430 mm	[ 27,56x15,75x16,93 in ]
Installation environment		Indoor	



## TOP MOUNTED MODEL

1900 W

